

AC/DC Mini Digital Clamp Tester

AC/DC Current AC/DC Voltage Resistance

Model 280 (CE)



Meets safety standard CAT.II 600V or CAT.III 300V

FEATURES

- 30mm ϕ CT window and ultra compact size
- Conform to IEC safety requirements
- Low cost and multi-function clamp tester
- Max. & Min.hold function
- Data-hold function and auto power off
- Auto zero adjustment for DC current offset

SPECIFICATIONS

Safety standard	:	IEC61010-1, IEC61010-2-032 Installation Category II 600V or CAT III 300V
E.M.C. standard	:	EN 61326
Measuring method	:	Dual slope integration mode
Display	:	4 digit LCD max. reading of 9999
Measuring range	:	AC Current 1000A DC Current 1000A AC Voltage 500V DC Voltage 500V Resistance 600Ω

Accuracy (23°C±5°C, 80%RH or less)

Range	Input range	Accuracy
AC Current (ACA)	0~600A	±1.5%rdg±8dgt
	600.1~999.9A	±3%rdg±8dgt
DC Current (DCA)	0~±600A	±1.5%rdg±6dgt
	±600.1~±999.9A	±3%rdg±6dgt
AC Voltage (ACV)	0~500V	±1.0%rdg±8dgt
DC Voltage (DCV)	0~500V	±1.0%rdg±6dgt
Resistance (Ω)	0~600Ω	±1.5%rdg±8dgt

Jaw opening capability	:	30mm φ
Over range indication	:	" OL " mark on LCD.
Auto power off	:	Approx.10 minutes later after power on
Polarity	:	“—” sign for negative polarity
Low battery indication	:	“ B ” mark on LCD
Data hold indication	:	“DH” mark on LCD
Max. memory function	:	“Max” mark on LCD with max. value
Min. memory function	:	“Min” mark on LCD with min. value
DC current zero offset	:	By push button switch
Sampling time	:	2 times/sec
Limitation of circuit voltage	:	Less than AC/DC 600V
Withstanding voltage	:	AC 3700V 1 minute max. (Between the core of CT and outer case)
Operating temperature	:	0°C ~ 40°C<80%RH (without condensation)
Storage temperature	:	-10°C ~ 60°C<70%RH (without condensation)
Power supply	:	LR-44×2
Battery life	:	Approx.6 hours continuous
Power consumption	:	Approx.12mW
Size	:	44.5(W)×177(H)×24(D)mm
Weight	:	Approx. 95g
Accessories	:	Soft case.....1 Batteries, LR-44(1.55V).....2 Instruction manual.....1 Test lead.....1