



DATASHEET RFSG2,4,6

Specification v2.20

Signal Generators from 9 kHz to 2000 MHz, 4000 MHz and
6100 MHz



DEFINITIONS

- The specifications in the following pages describe the warranted performance of the instrument for 23 ± 5 °C after a 30-minute warm-up period (unless otherwise stated).

Min/Max: Parameter range that is guaranteed by product design, and/or production tested. Warranted performance specifications include guard-bands to account for the expected statistical performance distribution, measurement uncertainties, and changes in performance due to environmental conditions.

Typical: Expected mean values, not warranted performance.

INTRODUCTION

- RFSG2,4,6 models comprises a set of very compact, portable analog signal generator models from 9 kHz up to 6100 MHz. A combination of good signal purity, fast switching speed and wide dynamic range makes these units useful for a variety of applications.**

The RFSG2,4,6 is a series of a low-noise and fast-switching analogue signal generator covering a frequency range from 9 kHz up to 2.0, 4.0, and 6.1 GHz, respectively.

The RFSG2,4,6 provides full RF signal generator capabilities including OCXO-stabilized low phase-noise signal with micro-Hz frequency resolution, wide and accurately levelled output power range, extensive modulation capabilities, and fast switching.

It is targeted for a wide range of applications where a high-quality analogue signal is mandatory, offering an alternative to expensive high-end RF signal generators, where small size and excellent RF performance at an attractive cost is required.

The very compact and rugged design of the RFSG2,4,6 operates at very low DC power consumption (only 12 watts), with minor heat dissipation and not requiring noisy fan. This gives the RFSG2,4,6 a great advantage in laboratories or production test facilities.

The low power design allows the use of optional internal battery modules which make it a truly portable instrument, ideally suited for field testing, installation, and maintenance.

Available Options:

Option PE3 is an optional power level extension to accurately level below -120 dBm.

Option B3 adds an internal rechargeable battery module

Option AVIO adds dedicated avionics modulation like VOR/ILS

19-inch rack-mount solutions are also available.

The RFSG2,4,6 support various standard interfaces such as USB (USBTMC), LAN (VXI-11), or GPIB and extensive API with programming examples are available.

SPECIFICATIONS

PARAMETER	MIN	TYPICAL	MAX	NOTE
Frequency range	9 kHz		2.0 GHz 4.0 GHz 6.1 GHz	RFSG2 RFSG4 RFSG6
resolution		0.001 Hz		
Phase resolution		0.1 deg		
Settling time		20 µs 20 µs	100 µs 200 µs	<= SN xx-xxx2xxxxx-xxxx >= SN xx-xxx3xxxxx-xxxx
Frequency update rate		400 µs		time from receipt of SCPI command firmware
List/Sweep mode		400 µs		
SSB Phase noise at 1 GHz				
at 20 kHz from carrier		-130 dBc/Hz		See measured phase noise plots
Total jitter		68 fs RMS		10 Hz to 1 MHz BW
Spectral purity				
Output harmonics		-40 dBc	-30 dBc	$P_{out} = +10 \text{ dBm}$
Sub-harmonics		-80 dBc	-70 dBc	
Non-harmonic spurious < 1 MHz		-70 dBc	-60 dBc	$P_{out} = +10 \text{ dBm}$
> 1 MHz		-75 dBc	-65 dBc	
Residual FM @ 1 GHz			3 Hz	0.3 kHz to 3 kHz, weighted (ITU-T)
			12 Hz	0.03 kHz to 23 kHz
Power level				
Range Without Option PE3	-30 dBm		18 dBm typically	> 10 MHz See plots on page 8
With Option PE3	-120 dBm		17 dBm typically	
Resolution		0.01 dB		
Level uncertainty		0.3 dB 0.5 dB 1.5 dB	< 0.8 dB < 1.3 dB	-20 to + 10 dBm -80 to -20 dBm < -80 dBm
Output impedance VSWR		50 Ω 1.5 1.7	1.8 2.0	< 3 GHz > 3 GHz
Reference frequency input	8 MHz		200 MHz	User programmable
Reference input level	-5 dBm	0 dBm	+13 dBm	
Lock Range			+/- 1.0 ppm	
Reference input impedance		50 Ω		
Internal reference frequency output		10 MHz		

Initial accuracy of internal reference		± 40 ppb		calibrated at 23 ± 3 °C at time of calibration
Temperature stability (0 to 50 degC)			± 100 ppb	
Aging 1 st year		0.5 ppm		
Aging per day (after 30days operations)			5 ppb	
Warm-Up time		5 min		
Output of internal reference		+0dBm 50 Ω		
Reverse Power Protection				
DC Voltage		30 V		
RF power			36 dBm	
Dimensions				
Excluding connectors		W x L x H = 172 x 250 x 106 mm		
Including connectors		W x L x H = 172 x 273 x 106 mm		



Sweeping Capability

Sweeps can be performed with combined internal or external AM/FM/PM/pulse modulation running. With modulation enabled, the minimum step time increases to 2 ms.

PARAMETER	MIN	TYPICAL	MAX	NOTE
Frequency sweep				
Sweep type: linear, logarithmic, random				
Step time (t_{step})	400 μs		19998 s	
Dwell time (t_{dwell})	50 μs		9999 s	
Off-time (incl. transient time) (t_{off})	0 / 50 μs		9999 s	
Timing accuracy per point		1 μs		
Generalized list sweep				
allows individual setting of frequency, power, dwell-time, and off-time for each point				
List size	2		20.000	
Step time (t_{step})	200 μs		19998 s	
Dwell time (t_{dwell})	50 μs		9999 s	
Off-time (incl. transient time) (t_{off})	0 / 50 μs		9999 s	
Time resolution		0.1 μs		
Timing accuracy per point		1 μs		
Frequency Chirps (linear ramp, up/down)				
Bandwidth			10%	
Dwell time (t_{dwell})	10 ns		100 μs	
Number of frequencies			20'000	



Modulation Capabilities

All modulation types (FM, PM, AM, and pulse modulation) may be simultaneously enabled except: FM and phase modulation cannot be combined. For example, AM and FM can run concurrently and will modulate the output RF.

PARAMETER	MIN	TYPICAL	MAX	NOTE
Pulse modulation				
On/off ratio		70 dB		
Repetition frequency	DC		33 MHz	
Pulse width	30 ns 50 µs		20 s 20 s	ALC hold ALC on
Pulse rise/fall time		5 ns		
Pulse trainslength (pulses)	2		4192	
Video crosstalk		-40 dB		
External input amplitude		1 V TTL		AC DC
Delay (to RF)		20 ns	40 ns	
Frequency modulation		> 2 MHz N x 100 MHz		< 0.37 GHz 0.37 GHz to 0.75 GHz (N=0.125) 0.75 GHz to 1.5 GHz (N=0.25) 1.5 GHz to 3 GHz (N=0.5) > 3 GHz to 6.1 GHz (N=1)
Modulation waveforms		Sine, triangle, FSK		
Modulation rate	1 Hz/DC		800 kHz	-3dB frequency response Max. phase deviation degrades above 20 kHz modulation rate
External input sensitivity		< N · 100 MHz for 1 Vpp		settable in AC mode discrete values in DC mode
Total harmonic distortion		< 1%		1 kHz rate & N · 100 kHz deviation
Phase modulation				
Phase deviation (peak)	0		N·80 rad	
Modulation rate	1 Hz		800 kHz	> -3dB frequency response
Modulation waveforms		Sine, triangle, FSK		
External Input sensitivity		N · 40 rad for 1 Vpp		
Total harmonic distortion		< 1%		1 kHz rate & N · 20 rad deviation
Amplitude modulation				
Modulation rate	10 Hz 10 Hz		20 kHz 50 kHz	applies for internal and external => SN xx-xxx5xxxxx-xxxx
Modulation depth	0 %		95 %	
Modulation waveforms		Sine, triangle, square		
Distortion		2 %		
Accuracy		3 %		
External inputsensitivity		X % per 1 Vpp		settable

Avionics Modulation (option AVIO)

ILS		
Localizer RF frequency	108 to 112 MHz	
Nominal tone frequencies	90 & 150 Hz	
Frequency accuracy	< 0.02 Hz	
Centerline (in %)	DDM: 0 ± 0.1 ; SDM: 40 ± 2.0	
Fly left (in %)	DDM: 15.5 ± 0.5 ; SDM: 40 ± 2.0	
Fly right (in %)	DDM: -15.5 ± 0.5 ; SDM: 40 ± 2.0	
Flag (in %)	DDM: 0 ± 0.1 ; SDM: 30 ± 2.0	
Glide Path RF frequency	328.6-335.4 MHz	
Angle of Descent (in %)	DDM: 0 ± 0.1 ; SDM: 80 ± 3.0	
Fly up (in %)	DDM: 17.5 ± 0.5 ; SDM: 80 ± 3.0	
Fly down (in %)	DDM: -17.5 ± 0.5 ; SDM: 80 ± 3.0	
Flag (in %)	DDM: 0 ± 0.1 ; SDM: 70 ± 2.5	
VOR RF frequency	108 - 118 MHz	
Subcarrier Frequency	9960 ± 2.0 Hz	
FM deviation	480 Hz	
AM tone	30 ± 0.02 Hz	
Bearing north	TDM: 30 ± 2.0 %	
Bearing south	Phase: 180 ± 0.5 deg	
Bearing east	TDM: 30 ± 2.0 %	
Bearing west	Phase: 90 ± 0.5 deg	
Test 1	TDM: 30 ± 2.0 %	
Test 2	Phase: 0 ± 0.5 deg	



Multi-Purpose Output (FUNC OUT)

Output is FUNC OUT at rear panel

PARAMETER	MIN	TYPICAL	MAX	NOTE
MULTIFUNCTION GENERATOR				
sine, triangle, square wave				
Frequency range	1 Hz 1 Hz		3 MHz 1 MHz 50 kHz	sine triangle square
Frequency resolution		0.1 Hz		
Output voltage amplitude peak-peak	10 mV	5V	2 V	Sine, triangle Square (CMOS output)
Harmonic distortion		1 %		< 100 kHz, 1 Vpp
Output impedance		50 Ω CMOS		Sine, triangle squarewave
VIDEO OUTPUT (of internal pulse modulator)				
Output		CMOS		
Period	30 ns		50 s	
Pulse Width	15 ns		50 s	
RF delay		10 ns		

TRIGGER OUT Synchronization mode for multiple sources

Modes	Trigger on sweep start Trigger on each point		
Trigger waveform pulse width		100 ns	


Trigger (TRIG IN)

Input is TRIG IN at rear panel

PARAMETER	MIN	TYPICAL	MAX	NOTE
Trigger Types		Continuous, single, gated, gated direction		
Trigger Source		RF key, external, bus (GPIB, LAN, USB)		
Trigger Modes		Continuous free run, trigger and run, reset and run		
Trigger latency		tbd		
Trigger uncertainty		5 µs		
External Trigger delay	50 µs		40 s	
External Delay Resolution		15 ns		
Trigger Modulo	1		255	Execute only on Nth trigger event
Trigger Polarity		Rising, falling		


PERFORMANCE CURVES

• Typical Maximum Output Power (without option PE3)




Typical Maximum Output Power (WITH option PE3)

Maximum Output Power (1 kHz to 10 MHz)




Phase Noise Performance (1,2 and 4 GHz)







Harmonic performance at + 10 dBm



Connectors (Front)



Connectors (Rear)



1. RF output: N female
2. RF on/off button
3. Rotary knob
4. Menu and $\downarrow\uparrow\leftarrow\rightarrow$ arrow keys

1. Trigger input: BNC female
2. Function output: BNC female
3. External reference input: BNC female
4. Internal reference output: BNC female
5. FM/PM modulation input: BNC female
6. AM and Pulse modulation: BNC female
7. LAN connection: RJ-45
8. USB 2.0 host and device
9. GPIB: IEEE-488.2, 1987 with listen and talk (optional)
10. DC Power plug (6V, 6 A)
11. DC power switch

ORDERING INFORMATION

HOST MODEL	PRODUCT	DESCRIPTION
RFSG2,4,6	RFSG2	9 kHz – 2000 MHz Signal Generators
RFSG2,4,6	RFSG4	9 kHz – 4000 MHz Signal Generators
RFSG2,4,6	RFSG6	9 kHz – 6100 MHz Signal Generators
RFSG2,4,6	B3	Internal rechargeable battery module
RFSG2,4,6	GPIB	GPIB interface
RFSG2,4,6	AVIO	Avionics modulation capability (VOR/ILS)
RFSG2,4,6	1URM	1U rack-mount module
RFSG2,4,6	REAR	Move output to the rear panel
RFSG2,4,6	OEM	OEM package
RFSG2,4,6	WE	One-year warranty extension (standard: 2 years)
RFSG2,4,6	ReCal	Recalibration with test data (recommended: two years interval)

GENERAL CHARACTERISTICS

Remote programming interfaces

Ethernet 100BaseT LAN interface

USB 2.0 host & device

GPIB (IEEE-488.2,1987) with listen and talk (optional)

Control language SCPI Version 1999.0

Power requirements: 6 VDC; 20 W maximum

Mains adapter supplied: 100-240 VAC in/ 6 V 6.0 A DC out

Storage temperature range –40 to 70 °C

Operating temperature range 0 to 45 °C

Operating and storage altitude up to 15,000 feet



Safety/EMC complies with applicable Safety and EMC regulations and directives.

Weight ≤ 2.5 kg (6 lbs) net, ≤ 4 kg (8 lb.) shipping

Dimensions:

116.9 mm H x 173.6 mm W x 270.7 mm L (incl. connectors)
[4.60 in H x 6.83 in W x 10.66 in L]

Recommended calibration cycle 24 months

Compatibility languages supporting commonly used commands

Agilent Technologies N5181A MXG, Aeroflex, Rohde & Schwarz SMA and SML models



Document History

AnaPico Ltd. of Switzerland

Europastrasse 9
8152 Glattbrugg
Switzerland

Phone +41 44 440 00 50
Email sales@anapico.com

www.anapico.com
www.anapico.com/downloads/

NOTES